爱勒普科技
ALP Technology

PULL ROD BOX POWER STATION



Model		ALP2K2304	ALP1K1152	ALP3K2688	ALP3K3200	ALP3K4378	ALP5K5376
Battery	Energy(Wh)	2304	1152	2688	3200	4378	5376
	Standard voltage	51.2V	25.6V	25.6V	25.6V	25.6V	51.2V
	Charge protection voltage	58.4V	29.2V	29.2V	29.2V	29.2V	58.4V
	Discharge protection voltage	40V	20V	20V	20V	20V	40V
	Charging temperature range	0-55℃(32F-131F)					
	Discharge temperature range	-20-65℃(4T-149F)					
	Relative humidity	45%~85%(113F-185F)					
	Storage(within 1 month)	-20℃~45℃(4F-113F)					
	Storage(within 1 year)	0℃~35℃(32F-95"F)					
	Storage humidity	⩽70%					
	Charge Curent(A)	⩽20	⩽20	⩽35	⩽40	⩽40	⩽30
	Maximum discharge curent (A)	⩽60	⩽60	⩽120	⩽120	⩽120	⩽120
Appearance	Weight(kg)	20-25	15-20	35-40	40-45	45-55	60-65
	Dimension high*width*depth(mm)	380*280*230	405*380*265	405*380*265	435*380*265	475*485*330	550*515*385
Inverter (multifunctional)	AC voltage input/frequency	110V/220V(50/60Hz)					
	AC voltage output/ frequency/ efficiency	110V/220V(50/60Hz)/(⩾90%)					
	PV Input	12-60V20A	12-30V20A	30-90V40A	30-90V40A	120-500V30A	120-500V30A
	AC Output Power	1200W	600W	3000W	3000W	5000W	5000W
	With UPS function	YES					
DC Output	USB Output-2PCS	18W					
	PD-2PCS	18W					
	DC Output-1PCS	12V/10A					
Solar Panel(Optional)	Power	⩽800W	600W	⩽1600W	⩽1600W	⩽1600W	⩽4400W

Wuxi ALP Technology Co., Ltd
Add: No.2610, Building 8, 3rd Financial Street, Binhu District, Wuxi, China
Email: evanzhang@ks-alp.com
Web: www.wx-alp.com
TEL/Wechat: +86 13621950365
WhatsApp: +86 18851503628